AMENDMENTS TO THE CLAIMS

Docket No.: HO-P02932US0

- (Currently amended) An additional filter element of a filter apparatus for reducing emissions from a tank venting system, which in use is connected to a main activated carbon filter, the additional filter element comprising:
 - wherein the additional filter element has at least one adsorbent which to achieve a high working capacity, in particular at 42°C, has a high micropore volume and which to retain a residual loading which is possibly present in the micropores has a mesopore volume: and
 - a filter body with a rear side and a small adsorptive additional element at said rear side, said additional filter element being adapted to produce a relatively small pressure drop and having an adsorption capacity at 25°C with an n-butane concentration of between 5 and 50% by volume of greater than 35 g of n-butane per liter.
- 2. (Currently amended) <u>The An</u> additional filter element as set forth in claim 1 wherein the micropore volume is at least 0.4 cm³/g.
- 3. (Currently amended) <u>The An</u> additional filter element as set forth in claim 2 wherein the micropore volume is at least 0.7 cm³/g.
- 4. (Currently amended) <u>The An</u> additional filter element as set forth in claim 1 wherein the mesopore volume is at least 0.15 cm³/g.
- 5. (Currently amended) <u>TheAn</u> additional filter element as set forth in claim 4 wherein the mesopore volume is at least 0.25 cm³/g.

3

6. (Currently amended) <u>The An</u> additional filter element as set forth in claim 4 wherein the mesopore volume is at a maximum 0.95 cm³/g.

Docket No.: HO-P02932US0

- 7. (Currently amended) <u>The An</u> additional filter element as set forth in claim 6 wherein the mesopore volume is at a maximum 0.35 cm³/g.
- 8. (Currently amended) <u>The An</u> additional filter element as set forth in claim 1 <u>including wherein athe</u> filter body hagving a honeycomb structure.
- 9. (Cancelled)
- 10. (Currently amended) The An additional filter element as set forth in claim 9 wherein said additional filter element is including a carrier body comprising a three-dimensional fiber matrix with adsorber particles fixed therein.
- 11. (Currently amended) The An additional filter element as set forth in claim 19 wherein said additional filter element is formed by a pressed highly porous activated carbon body in the form of a sieve, said body comprising adsorber particles of a coarse grain fraction and a binding agent joining said adsorber particles together.
- 12. (Currently amended) TheAn additional filter element as set forth in claim 11 including a filter body having a honeycomb structure, and wherein the pressed activated carbon body is fixed to the honeycomb structure filter body by means of said binding agent.

Docket No.: HO-P02932US0

- 13. (Currently amended) <u>The An</u> additional filter element as set forth in claim 11 wherein said binding agent is a polyamide binding agent.
- 14. (Currently amended) <u>The An</u> additional filter element as set forth in claim 8 and further including a PCM layer enclosing the at least one honeycomb structure filter body and the additional element, said layer involving a phase change in a temperature range of between 35 and 45° C.
- 15. (Currently amended) <u>The An</u> additional filter element as set forth in claim 14 wherein said temperature range is between 39° C and 42° C.
- 16. (Currently amended) The An additional filter element as set forth in claim 8 wherein said honeycomb filter structure body comprises at least two honeycomb structure filter body portions.
- 17. (Currently amended) In a hydrocarbon fuel tank venting system a filter arrangement for reducing emissions from the tank venting system_, including comprising:

a main activated carbon filter; and an additional filter element connected to the main activated carbon filter;

wherein the additional filter element has at least one adsorbent which to achieve a high working capacity, in particular at 42°C has a high micropore volume of at least 0.4 cm³/g, and which to retain a residual loading possibly present in the micropores has a mesopore volume of at least 0.15 cm³/g.

18. (Currently amended) <u>The</u>A system as set forth in claim 17 wherein the micropore volume is at least 0.7 cm³/g.

Application No. 10/771,712 Amendment dated July 27, 2006 Reply to Office Action of February 28, 2006

Docket No.: HO-P02932US0

19. (Currently amended) <u>The</u>A system as set forth in claim 17 wherein the mesopore volume is at least 0.25 cm³/g.

20. (Currently amended) <u>The</u>A system as set forth in claim 17 wherein the mesopore volume is at a maximum 0.95 cm³/g.